SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2024 / Canada WHMIS 2023

Date issued : 04/25/2018
SDS number : Rust Check Rust Inhibitor aerosol - 1043 180g_EN
Date revised : 02/02/2026
Revision number : 4

1043 RUST CHECK RUST INHIBITOR, aerosol

1. Identification

Product identifier: 1043 RUST CHECK RUST INHIBITOR, aerosol
Product description: Lubricant / rust preventive, oil-based 180 g / 6.35 oz
Relevant identified uses of the substance or mixture and uses advised against: Rust Preventative Lubricant, aerosol
Other means of identification - product Stock / Code: 1043
Chemical family: Hydrocarbon oils
Molecular formula: Mixture

Manufacturer / Supplier
Rust Check Corporation
6175 Danville Road, Mississauga
Ontario, Canada L5T 2H7
Customer Service: 905-670-5411

Emergency telephone number
Telephone number to contact in the event of an emergency (9 am to 5 pm from M to F):
(905) 670-5411

2. Hazard identification

Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2024) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2023). This information may be different from the actual product label information for labels that are regulated by other agencies.

Health hazards:

Eye Irritation, Category 2B
Skin Sensitization, Category 1

Physical hazards:

Aerosols, Category 1
Simple Asphyxiants, Category 1

Label elements

Hazardous components for labelling:
calcium petroleum sulfonate, stoddard solvent and acetone

Flame

Exclamation mark

Signal word: DANGER

Hazard statement(s)

H222: Extremely flammable aerosol.

H229: Pressurized container: may burst if heated.
H320: Causes eye irritation.
H317: May cause an allergic skin reaction.
H600: May displace oxygen and cause rapid suffocation.

Precautionary statement(s)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P264: Wash hands thoroughly after handling.
P261: Avoid breathing mist, vapours or spray.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves and eye protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.

Storage:

P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

Hazards not otherwise classified: No data available.

Emergency overview

Immediate concerns: Extremely flammable aerosol. Causes eye irritation. Prolonged and repeated skin contact may lead to slight transient irritation in sensitive individuals. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Inhalation of oil mists may cause irritation of the upper respiratory tract. Oily deposits in the lungs may lead to pulmonary fibrosis and reduced pulmonary function. Vapor reduces oxygen availability for breathing.

Comments: See sections 9 and 10 for more detailed information on physicochemical effects.
See section 11 for more detailed information on health effects.
See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.
Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2023 and OSHA Hazcom 2024 Hazard Communication labeling.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	51 - 55	64742-65-0
mineral oils (petroleum) (non-hazardous ingredient)	19 - 21	8042-47-5
isobutane	9 - 11	75-28-5

propane	7 - 8	74-98-6
solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	3.5 - 4.5	64741-88-4
calcium petroleum sulfonate	3 - 4	61789-86-4
stoddard solvent	1 - 1.5	8052-41-3
acetone	0.5 - 1	67-64-1

Comments: The actual concentration is withheld as a trade secret.
There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

4. First-aid measures

Eye: Thoroughly flush the eyes with large amounts of clean water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

Skin: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Inhalation: If affected by inhalation of spray mist, move to fresh air. Get medical attention if symptoms persist.

Most important symptoms and effects, both acute and delayed

Eye: Mildly irritating to the eyes. Prolonged and repeated contact with the eyes may produce a slight transient irritation. Symptoms may include tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin: Substance does not generally irritate and is only mildly irritating to the skin. Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne. Symptoms may include redness, edema, drying and cracking of the skin. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Ingestion: May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

Inhalation: High spray mist concentrations may be harmful if inhaled. Avoid breathing mists. Inhalation of oil mists may cause irritation of the upper respiratory tract. Oily deposits in the lungs may lead to pulmonary fibrosis and reduced pulmonary function. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

Indication of immediate medical attention and special treatment needed, if necessary: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Additional information: No data available.

5. Fire-fighting measures

General hazard: Extemely flammable aerosol. Can readily form explosive mixtures at or above the flash point. Product can be ignited by static discharge.

Suitable extinguishing media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Hazardous combustion products: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire fighting procedures: Containers can build up pressure if exposed to heat (fire).

Fire fighting equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Sensitivity to static discharge: Product is sensitive to static discharge.

Sensitivity to mechanical impact: Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120°F (49°C).

6. Accidental release measures

Small spill: Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

Environmental precautions

Water spill: Do not flush to sewer.

Land spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Special protective equipment: Clean up spills immediately, observing precautions in Protective Equipment section 8.

7. Handling and storage

General procedures: Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

Precautions for safe handling: Contents under pressure. Do not expose to heat or store above 120°F (49°C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breath vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Conditions for safe storage: Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

8. Exposure controls/personal protection

Exposure controls

Control parameters				
	Occupational exposure limit values			
Chemical name	**Type**		**ppm**	**mg/m³**
solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	**OSHA PEL**	**TWA**	-- [1]	5 [1]
	ACGIH TLV	**TWA**	-- [1]	5 [1]
	NIOSH REL	**TWA**	-- [1]	5 [1]
		STEL	-- [1]	10 [1]
isobutane	**ACGIH TLV**	**STEL**	1000	--
	NIOSH REL	**TWA**	800	1900
propane	**OSHA PEL**	**TWA**	1000	1800
	ACGIH TLV	**TWA**	1000	--
	NIOSH REL	**TWA**	1000	1800
solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	**OSHA PEL**	**TWA**	-- [1]	5 [1]
	ACGIH TLV	**TWA**	-- [1]	5 [1]
	NIOSH REL	**TWA**	-- [1]	5 [1]
		STEL	-- [1]	10 [1]
calcium petroleum sulfonate	**USA OEL**	**-**	[2]	[2]
stoddard solvent	**OSHA PEL**	**TWA**	500	2900
	ACGIH TLV	**TWA**	100	572
acetone	**OSHA PEL**	**TWA**	1000	2400
	ACGIH TLV	**TWA**	500	1188
		STEL	750	1782
	NIOSH REL	**TWA**	250	590

Footnotes:
1. Oil mist, mineral
2. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.

Appropriate engineering controls: If user operations generate mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Avoid breathing mists; if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices.

Individual protection measures, such as personal protective equipment

Eye / face protection: Wear safety glasses with side shields (or goggles).

Skin: Wear chemical resistant gloves. Avoid prolonged or repeated contact with skin.

Respiratory protection: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Skin protection - other: Not applicable for aerosol containers.

Occupational hygiene practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

9. Physical and chemical properties

Physical State: Liquid, without aerosol propellants

Odour: Characteristic

Odour threshold: No data available.

Appearance: Aerosol

Colour: Red

pH: Not Applicable

% Volatiles: 22 - 25% w/w

Flash point: > -18°C Closed Cup [lowest known value of aerosol concentrate]

Lower explosion limit / flammability limit: 1

Upper explosion limit / flammability limit: 12.8

Auto-ignition temperature: No data available.

Vapour pressure: 55 - 75 psig at 20°C

Relative vapour density: > 1 (air = 1)

Initial boiling point and boiling range: 56°C (acetone) [lowest known value of aerosol concentrate]

Freezing point: No data available.

Melting point: No data available.

Decomposition temperature: No data available.

Solubility: Practically insoluble

Partition coefficient n-octanol/water (logarithmic value): No data available.

Evaporation rate (n-butyl acetate = 1): > 1

Density: 0.84-0.90 g/ml at 20°C

Notes: An estimate for the aerosol concentrate density

Particle characteristics: No data available.

Relative density: No data available.

Viscosity (kinematic or dynamic): 70 to 120 cps (Aerosol concentrate) at 20°C

VOC content: 21 - 24% w/w

Flammability: Flammable Liquids

Comments:

Flammability Statement:

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability:	Yes
Aerosol Flame Projection:	<80 cm
Flashback:	Yes
Calculated Aerosol Chemical Heat of Combustion, kJ/g	31 to 35

VOC Compliance Statement

Total Volatiles: 22 - 25% w/w
VOC Content: 21 - 24% w/w, less exempts
PWR(PWMIR): 0.55 to 0.59 g O_3/g product

VOC Regulation: Canada – VOC Concentration Limits for Certain Product Regulations
Product Category: Rust Preventative or Rust Control Lubricant, aerosol
The VOC content meets the 25% w/w VOC limit for Rust Preventative, aerosol. Canada compliant.

VOC Regulation: California – Regulation for Reducing Emissions from Consumer Products – Title 17, California
Product Category: Rust Preventative Lubricant, aerosol
The product VOC content meets the current 25% w/w limit under the CARB Consumer Product Regulations for Rust Preventative Lubricant, aerosol. California compliant.

VOC Regulation: UT, LADCO & OTC States - Consumer Product Regulations
Product Category: Multi-Purpose Lubricant
The product VOC content meets the current 50% w/w limit under the above Consumer Product Regulations for Multi-Purpose Lubricant. Compliant.

VOC Regulation: USA National VOC Emission Standards for Aerosol Coatings – 40CFR PART 59 SUBPART E
Coating Category: Flat Coating Product
The VOC content meets the 0.80 PWR category limit for Flat Coating Product. USA compliant.

Restrictions on Sale:

None known.
Check for compliance in your area before using.

10. Stability and reactivity

Reactivity: No

Dangerous polymerization: Not expected to occur.

Chemical stability: Stable.

Conditions to avoid: Keep away from flames and any object that sparks. Container may expode if heated.

Possibility of hazardous reactions: No data available.

Hazardous decomposition products: Carbon Monoxide and other toxic vapors.

Incompatible materials: Oxidizing materials.

11. Toxicological information

Acute Toxicity

Chemical name	LD_{50} (oral) mg/kg(rat)	LD_{50} (dermal) mg/kg(rabbit)	LC_{50} (inhalation) mg/l
solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	> 5000	> 5000	>5.0(rat;4h - mist)
isobutane	Not Applicable	Not Applicable	658(rat;4h) 570,000 ppm (rat;15m) 680(mouse;2h)
propane	Not Applicable	Not Applicable	>800,000 ppm (rat,15m) [>1443 mg/L]
solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	> 5000	> 5000	>5.0(rat;4h - mist)
calcium petroleum sulfonate	> 2000	> 2000	No data available.
stoddard solvent	> 5000	> 3000	8.5(rat;8h) >5.5(rat;4h)
acetone	8400 5250(mouse) 5300(rabbit)	>15,700	50.1(rat;8h) 44.0(mouse;4h)

Acute dermal toxicity LD_{50}: Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute oral toxicity LD_{50}: Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute inhalation toxicity LC_{50}: Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists).

Notes: <5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.
No additional toxicology information is available for this product itself.
(See Component Toxicity Information).

Skin corrosion / irritation: Based on available data, the classification criteria for skin irritation are not met for this mixture. Substance does not generally irritate and is only mildly irritating to the skin. Prolonged contact with this product may cause an allergic skin reaction. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

Serious eye damage / irritation: The mixture is classified as: Eye Irritant, category 2B, based on ingredient data. Causes eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Respiratory or skin sensitization: Contains: calcium petroleum sulfonate. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data (≥ 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A or ≥ 1.0% ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.
Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

Germ cell mutagenicity: Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

Carcinogenicity

Chemical name	NTP	IARC	OSHA	Status - other
solvent-dewaxed heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	--	--	--	--
isobutane	--	--	--	--
propane	--	--	--	--
solvent-refined heavy paraffinic distillates (petroleum) (non-hazardous ingredient)	--	--	--	--
calcium petroleum sulfonate	--	--	--	--
stoddard solvent	--	--	--	--
acetone	--	--	--	A4 (ACGIH)

Notes: The mineral oils in this product are highly refined. Based on available data, the classification criteria for Carcinogenicity are not met for this mixture (< 0.1% ingredients classified as a Carcinogen, category 1 or 2). The mineral oils in this product are highly refined and are classified: Inadequate evidence for carcinogenicity of highly refined oils - IARC 1987.

Reproductive toxicity: Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture (< 0.1% ingredients classified as Reproductive Toxicity, category 1 or 2).

Specific Target Organ Toxicity - single exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Single Exposure are not met for this mixture (< 1.0% ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1 or 2 and < 20% summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3).

Specific Target Organ Toxicity - repeated exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Repeated Exposure are not met for this mixture (< 1.0% ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 1 or 2).

Aspiration hazard: Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture (< 10% ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm^2/s at 40 °C).

12. Ecological information

Ecotoxicological information: No data available.

Aquatic toxicity, both acute and chronic: No data available.

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

Mobility in soil: No data available.

13. Disposal considerations

Disposal methods: Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

Product disposal: When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: AEROSOLS

Transport hazard class(es): 2.1

UN number: 1950

Packing group, if applicable: N/AP

DOT other shipping information:
With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity as per DOT 173.306.

IMDG - sea

UN proper shipping name: AEROSOLS

UN number: 1950

Transport hazard class(es): 2.1

Packing group, if applicable: N/AP

Environmental hazards - marine pollutant: None

Hazard label: None

Notes: With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

Canadian Transport of Dangerouse Goods Regulations (TDG)

UN proper shipping name: AEROSOLS

UN number: 1950

Transport hazard class(es): 2.1

Packing group, if applicable: N/AP

TDG other shipping information:
With an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

15. Regulatory information

UNITED STATES

SARA Section 311/312 Hazard Categories

311/312 Health hazards: Eye Irritation, Simple Asphyxiants, Skin Sensitization

311/312 Physical hazards: Flammable Aerosols

EPCRA Section 313 Toxic Chemicals:
This product does not contain any listed toxic chemicals that exceed the threshold reporting levels established by SARA Title III, Section 313.

EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status:
This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

CERCLA Status:
This product contains no CERCLA listed hazardous substances.

Chemical name	% w/w	RQ
acetone	0.5 - 1	5,000

TSCA (The Toxic Substances Control Act)

TSCA Status:
All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) Hazardous Air Pollutants

CAA 112(r) List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(b).

This product contains the following chemicals subject to CAA 112(r).

Name	CAS No.	Threshold Qty (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

California Proposition 65:
This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

USA OSHA Hazard Communication Standard (29CFR 1910.1200):
OSHA Status: Hazardous Product (See Section 2 for details).
This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2024).

CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:
This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2023).

WHMIS Classification:
WHMIS 2023 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

Name	CAS No.	NPRI Part No.
stoddard solvent	8052-41-3	5 (VOC)
propane	74-98-6	5 (VOC)
isobutane	75-28-5	5 (VOC)

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):
All components are included or are otherwise exempt from inclusion on this inventory.

Comments VOC Content -- See section 9.

16. Other information

Reason for issue: The Safety Data Sheet was updated.

Approved by: Jim Gordon **Title:** R&D Chemist

Prepared by : Regulatory Compliance
Date revised: 02/02/2026

Information contact: 905-670-5411

Revision summary: This SDS replaces the 02/02/2026 SDS.

HMIS RATING

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		E

NFPA CODES



NFPA 30 / 30B Storage Classification: Level 3 Aerosol

Manufacturer supplemental notes: None

Data sources: Not Available

Additional SDS Information: N/AV Not Available
N/AP Not Applicable
ND Not yet determined
ACGIH American Conference of Governmental Industrial Hygienists
CAA The Clean Air Act
CCCR The Consumer Chemicals and Containers Regulations
CEPA The Canadian Environmental Protection Act
CERCLA Comprehensive Environmental Response, Compensation, and Liability Act
EPCRA The Emergency Planning and Community Right-To-Know Act
IARC International Agency for Research on Cancer
MSHA Mine Safety and Health Administration
NIOSH National Institute for Occupational Safety and Health
NTP National Toxicology Program
OSHA The Occupational Safety and Health Administration
SARA The Superfund Amendments and Reauthorization Act
WHMIS Workplace Hazardous Materials Information System

General statements: None

Comments: None

Manufacturer disclaimer: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.