

PRODUCT FEATURES & APPLICATION



Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

2K EUROPEAN FINISHING PUTTY

Stock XEP25

Part # 4601

Colour: White

2000g (64.45 oz)

Description:

European 2K Polyester Finishing Putty is an advanced tack-free putty designed for filling minor surface imperfections on body filler or steel, aluminum, galvanized metals and SMC. Spreads and sands easily with great feather-edging characteristics.

Features:

- State of the art technology
- Easily applied
- Finely ground finishing putty
- Easy sanding
- No clogging of sand paper
- Excellent topcoat finish

Surface Preparation:


- Sand repair area with 120 grit sand paper.
- Clean galvanized with acetone
- Remove all dirt, water, oil, rust etc.

Application Instructions:

1. Thoroughly mix putty with hardener
2. Apply to surface
3. Hardener amount should be equivalent to 2-3 % (by weight) of the putty.
4. DO NOT UNDER-USE HARDENER
5. Apply a thin layer with firm even strokes in one direction.
6. Repeat layers as needed or necessary

Finish:


1. Sand with finer grade abrasives.
2. Sand to a final contour after putty hardens (15 to 20 minutes).



2 % Hardener




4 to 5 min pot
life at 20C



20 to 30 min at
20 C or 68F



P120 to P280



Avoid Heat

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

Call 1-800-265-0790 or visit us on the web www.dominionsureseal.com