

PRODUCT FEATURES & APPLICATION

Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

TRIM BLACK

Stock STW1 / 24003 (Semi Gloss)
STW2 / 24007 (Flat)

Description: Dominion Sure Seal's Trim Black paints will restore faded and peeling paint from exterior trim parts. STW1 and STW2 are specially formulated to stick to properly cleaned and prepared metal, stainless steel chrome, and other plastic trim pieces. With STW1 and STW2 you can restore virtually any automotive trim piece to its black original color.

Features:

- No primer required – self etching to bare metal
- Fast coverage – increased pigment load
- Restores automotive trim pieces back to original black color.
- Refreshes faded black trim pieces
- Self Etching
- Fast Drying
- Minimal surface prep.
- Flat or Semi Gloss Black available
- Large 20 fluid oz can

Application Instructions:

1. Clean surface to be coated with Dominion Sure Seal Low VOC Cleaner (LVAPC)
2. Remove any rust and loose paint. Prime area if necessary.
3. Sand area to be coated with 400 – 600 grit sandpaper.
4. Re-clean with Dominion Sure Seal Low VOC Cleaner (LVAPC). Allow to dry thoroughly.
5. Shake can well before using.
6. Mask off areas not to be painted
7. Hold can 6 – 12 inches away from surface to be coated
8. Spray a medium wet coat until desired coverage is achieved. Allow the product to flash (3-5 min.) prior to applying additional coats. For best results apply with a sweeping motion. 1-2 medium wet coats is better than applying a heavy coat to avoid runs
9. Allow to dry prior to reassembly.
10. Use care when reassembling. Adhesion will continue to increase for up to 48 hours at 72 degrees F. (21 degrees C)
11. Clean nozzle when finish. Invert can and spray until no material is visible.