



DOMINION SURE SEAL LTD.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

Tel: 905-670-5411 / 1-800-265-0790 / Fax: 905-670-5174

www.dominionsureseal.com

D.U.N.S. 208 186 528

NO DRIP RUSTPROOFING, BLACK

STOCK: ASS512SBD	CODE: 1017	205 L (54.2 gal US) drum
STOCK: ASS512SBK	CODE: 1015	60.6 L (16 gal US) keg
STOCK: ASS512SBP	CODE: 10121	18.9 L (5 gal US) pail
STOCK: ASS512SB4L	CODE: 1024	4 L (1.06 gal US) jug

PRODUCT DESCRIPTION

Dominion Sure Seal No Drip Rustproofing Black is a solvent-free, high performance vehicle undercarriage protectant designed for use on both ferrous and non-ferrous metals. No Drip Rustproofing Black provides rapid water displacement and deposits a thin, translucent corrosion resistant film that will not gum under high humidity and high temperature conditions. No Drip Rustproofing Black contains no silicones and is harmless to most plastics and coatings.

PRODUCT APPLICATIONS

No Drip Rustproofing Black is a premium corrosion preventive compound with good metal adhesion and wash resistance, making it ideal for the treatment of motor vehicle undercarriage areas according to standard spraying methods. No Drip Rustproofing eliminates dripping from the undercarriage, but does not harden or dry out. It is self-healing, won't crack or peel and can be applied to both new and used vehicles. No Drip Rustproofing is also used for protection against rust and corrosion on automobile parts and accessories, fasteners of all types and various tools, jigs and fixtures. No Drip Rustproofing Black acts as both a low viscosity lubricating oil and corrosion preventive compound. The residual film provides good medium term protection against corrosion during metal part storage or covered transportation.

FEATURES

- Rapid water displacement;
- Water washout resistant;
- Good penetrating properties;
- High flash point;
- Pleasant odour;
- Free from heavy metals, such as Barium
- Thick, gel protective film;
- Almost zero VOC content.

TYPICAL PHYSICAL PROPERTIES – as supplied

Product	No Drip Rustproofing
Chemical Base	Petroleum oil
Appearance / Consistency	Thixotropic gel; extremely light grease
Colour / Odour	Translucent Black, cherry odour
Density at 20°C, lb/gal (g/ml) - approx.	7.26 ± 0.08 (0.87 ± 0.01)
Viscosity at 20°C, cps (#5sp @ 10 RPM)	4000 – 6000
Flash Point, COC, °C	> 200
Volatile Organic Content (VOC), g/L (lb/gal)	< 50 (0.40)

6175 Danville Road, Mississauga, ON Canada L5T 2H7

Ph: 905-670-5411

Fax: 905-670-5174

www.dominionsureseal.com



DOMINION SURE SEAL LTD.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

Tel: 905-670-5411 / 1-800-265-0790 / **Fax:** 905-670-5174

www.dominionsureseal.com

D.U.N.S. 208 186 528

TYPICAL PERFORMANCE PROPERTIES – as applied

Product	No Drip Rustproofing
Type of film	very light grease; oily
Drying Time at 70°F (21°C), minutes	Non-drying
Recommended Film Thickness, µm (mils)	75 – 180 (3 – 7)
Water Displacement	Pass
Corrosion Protection, indoor storage, months	12 - 18
Corrosion Protection, outdoor storage[1], months	6 - 12
Note 1: Assumes protected / covered from the elements.	

DIRECTIONS FOR USE - SURFACE PREPARATION

1. For maximum protection it is recommended that metal surfaces are clean, dry and free of rust, oil and mill scale.
2. It is recommended that the metal substrate temperature is 10 to 30°C (50 to 86°F) at the time of application.

DIRECTIONS FOR USE - PRODUCT PREPARATION & APPLICATION

1. No Drip Rustproofing is formulated to be used as supplied. It is not necessary to mix the product prior to use, however, mixing will ensure a uniform consistency during application.
2. Do not thin No Drip Rustproofing.
3. It is recommended that both the product and ambient temperature are 10 to 30°C (50 to 86°F) at the time of application.
4. No Drip Rustproofing can be applied by spray, brush, or wiping.

STORAGE STABILITY

The product should be stored tightly closed in the original containers in cool, dry typical warehouse location at 10 - 27°C (50 - 80°F). Avoid exposure to sunlight. Rotate stock on a first in, first out basis. After use, ensure containers are tightly closed.

SAFETY PRECAUTIONS

Contains highly refined petroleum oils, carbon black and calcium alkylbenzenesulfonate. May irritate eyes. May cause an allergic skin reaction. Exposure to liquid or vapour during spray operations may cause slight irritation (dryness) of the eyes, skin and/or respiratory tract. Do not get in eyes or on skin. Wear suitable protective clothing, gloves and eye protection. Use only in a well-ventilated area. In case of eye contact, wash with plenty of water and see a doctor. In case of skin contact, wash with plenty of soap and water. If irritation persists, seek medical attention. **KEEP OUT OF REACH OF CHILDREN.**

For more information, please see our latest safety data sheet.

All figures, recommendations and safety precautions are based on thorough investigations and our actual experience and are without engagement. Although the documentation has been set up with most carefulness, we do not accept any responsibility for mistakes, inaccuracies or printer's errors. We reserve the right to adjust the product, whenever we feel necessary. Because the design, the quality of the substrate and the conditions during application fall beyond our control, no responsibility for executed works can be accepted on the basis of this documentation. We therefore recommend to carry out own tests on the spot.
All our deliveries are subject to the General Terms and Conditions of Sale and Purchase of Dominion Sure Seal Ltd.